

0 601 216 1FD – GSB 10 RE


Material number	0 601 216 1FD	0 601 216 1F3	0 601 216 1F4	0 601 216 1F6	0 601 216 1F7	0 601 216 1F8	0 601 216 1K1
EAN	3165140848	3165140548076	3165140548083	3165140709118	3165140709125		3165140379250
100 pcs accessory 2 607 002 554				✓			
100 pcs accessory set			✓				
Keyed chuck 10 mm 2 608 571 078		✓	✓				✓
Tool box 1 600 A00 12S					✓		
Tool box 2 609 160 136						✓	



Technical data

Technical Data

Rated power input	500 W
No-load speed	0 - 2600 rpm
Power output	250 W
Weight without cable	1,5 kg
Drill spindle connecting thread	3/8"-24 UNF
Chuck capacity	1 - 10 mm
Impact rate at no-load speed	0 - 41600 bpm



Drilling range

Drilling dia. in concrete	10 mm
Drilling dia. in wood	20 mm
Drilling dia. in steel	8 mm

Sales information

Key Message

- Compact power – The most compact and powerful impact drill in its class

User benefits

- Robust and powerful 500 W motor
- Extremely compact for working in tight spaces and overhead
- Low weight of only 1.5 kg for fatigue-free working

Other features

- Forward/reverse rotation
- Electronic control for exact pilot drilling
- Rotating brush plate for constant power in reverse and forward rotation
- Higher dynamic load rated ball bearing for long life
- Ergonomic handle for comfortable use

