

MIG200G



C N-RYH-H01G-A0



Features:

1. Multi-Functional MIG, MMA.
2. Soft-Arc and Strong-Arc Adjustable.
3. Arc Stability with Low Spatter.
4. Pre-set Digital Display.
5. Wide Range for Input Voltage: 220V±15%.
6. With Advanced Single IGBT Technology.
7. Super Compact & Portable.



Applications:

- Education
- Maintenance, Repair
- Light & Medium Fabrication
- Construction
- Steel Erection

Specification:

V_{IN} AC220V±15% 1P	Input Frequency 50/60	A_{IN} MIG 37.4A MMA 33.2A	V_O 60V	P₁ Input Power MIG 8.2KVA MMA 7.3KVA	I₂ Current range MIG 40-200A MMA 30-160A	DUTY CYCLE 60%	Φ 220.73
η 80%	Wire-feeding Speed 3-13M/min (mm)	Wire-feeding Mechanism Internal	IP Protection Class Ip21	Wire Diameter 0.6-1.0mm	Weight 21kg	W_H × L 467×243×447 (mm)	

Standard Accessories:



MIG-15 3m
R-11-030100-19-00



300A+25mm² x 3m
N-52-DQ3A-250350A0



200A+16mm² x 3m
N-52-HQ2A-160350A0