



ATULARC®

PRODUCT **CATALOGUE**

MANUFACTURER & EXPORTER OF WELDING EQUIPMENTS

ONE STOP FOR ALL
WELDING
SOLUTIONS



IS : 2641



CM/L - 8530033811



ATULARC®

IS : 2641



CM/L - 8530033811

01

WELDING ELECTRODE HOLDERS

A 01

BASE BODY - MS & COPPER
INSULATION - D.M.C. (FIRE & HEAT PROOF)



A

60% : 600 Amp



3.15-4.00 mm

A

72 Pcs.


A 02

BASE BODY - MS & BRASS
INSULATION - NYLON GLASS FIELD



A

60% : 600 Amp



3.15-4.00 mm

A

100 Pcs.

A 03

BASE BODY - MS
INSULATION - NYLON GLASS FIELD



A

200 Amp



3.15 mm

A

100 Pcs.

A 04

BASE BODY - FULL BRASS
INSULATION - D.M.C. (FIRE & HEAT PROOF)



A

60% : 600 Amp



3.15-5.00 mm

A

72 Pcs.



A 05

BASE BODY - FULL BRASS
INSULATION - D.M.C. (FIRE & HEAT PROOF)



A

60% : 600 Amp



3.15-5.00 mm



72 Pcs.

IS : 2641



A 06

BASE BODY - FULL COPPER
INSULATION - D.M.C. (FIRE & HEAT PROOF)



A

60% : 600 Amp



3.15-5.00 mm

A

72 Pcs.

IS : 2641



info@atularc.com



www.atularc.com



ATULARC®

IS : 2641



CM/L - 8530033811

02

WELDING ELECTRODE HOLDERS

A 07

BASE BODY - FULL BRASS
INSULATION - D.M.C. (FIRE & HEAT PROOF)



A

60% : 600 Amp



3.15-4.00 mm



72 Pcs.

A 08

BASE BODY - FULL BRASS
INSULATION - NYLON GLASS FIELD



A

60% : 600 Amp



3.15-4.00 mm



100 Pcs.

A 09

BASE BODY - FULL BRASS
INSULATION - D.M.C. (FIRE & HEAT PROOF)



A

60% : 600 Amp



3.15-4.00 mm



100 Pcs.

A 10

BASE BODY - MS & COPPER
INSULATION - NYLON GLASS FIELD



A

60% : 600 Amp



3.15-4.00 mm



72 Pcs.

A 11

BASE BODY - FULL COPPER
INSULATION - D.M.C. (FIRE & HEAT PROOF)



A

60% : 600 Amp



3.15-5.00 mm



72 Pcs.



IS : 2641

A 12

BASE BODY - MS & COPPER (5 COPPER STRIPS)
INSULATION - D.M.C. (FIRE & HEAT PROOF)



A

60% : 600 Amp



3.15-4.00 mm



72 Pcs.



info@atularc.com



www.atularc.com



ATULARC®

IS : 2641



CM/L - 8530033811

03

WELDING ELECTRODE HOLDERS

A 13

BASE BODY - MS & COPPER (4 COPPER STRIPS)
INSULATION - D.M.C. (FIRE & HEAT PROOF)



A

60% : 600 Amp



3.15-4.00 mm



72 Pcs.


A 14

BASE BODY - MS & COPPER (4 COPPER STRIPS)
INSULATION - D.M.C. (FIRE & HEAT PROOF)



A

60% : 600 Amp



3.15-4.00 mm



72 Pcs.

A 15

BASE BODY - MS & COPPER (2 COPPER STRIPS)
INSULATION - D.M.C. (FIRE & HEAT PROOF)



A

60% : 600 Amp



3.15-4.00 mm



72 Pcs.

A 16

BASE BODY - MS & COPPER (0 COPPER STRIPS)
INSULATION - D.M.C. (FIRE & HEAT PROOF)



A

60% : 600 Amp



3.15-4.00 mm



72 Pcs.

A 17

SMALL EARTH CLAMP



A

400 Amp



130 Pcs.

A 18

BIG EARTH CLAMP



A

600 Amp



75 Pcs.



info@atularc.com



www.atularc.com



ATULARC®

IS : 2641



CM/L - 8530033811

04

WELDING ELECTRODE HOLDERS

A 19

WELDING HELMET
FLIP WINDOW TYPE



40 Pcs.

A 20

WELDING HAND SHIELD
FUSION



60 Pcs.

A 21

WELDING HAND SHIELD
(ATULARC HEAVY)



30 Pcs.

A 22

BASE BODY - MS & COPPER (8 COPPER STRIPS)
INSULATION - D.M.C. (FIRE & HEAT PROOF)



A

60% : 600 Amp



3.15-4.00 mm

72 Pcs.

A 23

BASE BODY - MS & COPPER
INSULATION - D.M.C. (FIRE & HEAT PROOF)

UNIQUE-1000



A

1000 Amp



3.15-5.00 mm

72 Pcs.

A 24

BASE BODY - MS & COPPER (10 COPPER STRIPS)
INSULATION - D.M.C. (FIRE & HEAT PROOF)

FUSION HY POWER



A

1000 Amp



3.15-5.00 mm

72 Pcs.



info@atularc.com



www.atularc.com



ATULARC®

IS : 2641



CM/L - 8530033811

05

WELDING ELECTRODE HOLDERS

A 25

BASE BODY - MS & COPPER (4 COPPER STRIPS)
INSULATION - D.M.C. (FIRE & HEAT PROOF)

TURBO



A

60% : 600 Amp



3.15-5.00 mm



72 Pcs.



IS : 2641

A 26

BASE BODY - MS & COPPER
INSULATION - D.M.C. (FIRE & HEAT PROOF)

TOP 200



A

60% : 600 Amp



3.15-4.00 mm



100 Pcs.

A 27

BASE BODY - MS & COPPER (10 COPPER STRIPS)
INSULATION - D.M.C. (FIRE & HEAT PROOF)

SUPER POWER



A

60% : 600 Amp



3.15-5.00 mm



72 Pcs.



IS : 2641

A 28

BASE BODY - MS
INSULATION - NYLON GLASS FIELD

FUSION MINI



A

400 Amp



3.15-4.00 mm



150 Pcs.

A 29

BASE BODY - MS
INSULATION - NYLON GLASS FIELD

FUSION SPARK




A

60% : 600 Amp



3.15-4.00 mm



72 Pcs.



info@atularc.com



www.atularc.com



ATULARC®

IS : 6901:2009



CM/L - 2717560

06

PRESSURE REGULATOR

FLOW-X



BASE BODY: 100% BRASS
BODY: FULL FORGED BODY
AVAILABLE GASES: O₂ / D.A / CO₂ / AR
GAUGES: SINGLE METER / DOUBLE METER

TANAKA



IS : 6901:2009



BASE BODY: 100% BRASS
BODY: FULL FORGED BODY
AVAILABLE GASES: O₂ / D.A / CO₂ / AR
GAUGES: DOUBLE METER

REGULATOR



BASE BODY: 100% BRASS
AVAILABLE GASES: O₂
GAUGES: SINGLE METER / DOUBLE METER

REGULATOR - DOUBLE STAGE



IS : 6901:2009



BASE BODY: 100% BRASS
BODY: FULL FORGED BODY
AVAILABLE GASES: O₂ / D.A / CO₂ / AR
GAUGES: DOUBLE METER

LPG-TORREX



100% BRASS WITH NUT
NIPPLE SET S.S. FINISH
APPROX. WEIGHT: 400 GRAM



LPG - TORR

100% BRASS WITH NUT
NIPPLE SET SET COMPACT TYPE

SIZE: 25mm
APPROX. WEIGHT: 230 GRAM





ATULARC®

IS : 7653:1975



CM/L - 2625555

07

LPG REGULATOR & GAS CUTTER

LPG - SINGLE METER



100% BRASS
SINGLE GAUGE

LPG - SINGLE METER



IS : 6901:1988



100% BRASS
SINGLE GAUGE

LPG - DOUBLE METER



IS : 6901:1988



100% BRASS WITH 2 GAUGES
& ADAPTOR

TORRENT



IS : 7653:1975



- BODY, HEAD & SOCKET MADE BY FORGED BRASS.
- MIXING PIPE MADE BY EXTRUDED BRASS ROD.
- ALL PIPES ARE OF HEAVY GAUGE BRASS / COPPER.
- ALL BRAZING DONE BY 43% SILVER ROD.
- CUTTING VALVE FITTED WITH DOUBLE O-RING.
- BOTH CONTROL VALVES ARE MADE OF S.S. FOR LONGER LIFE.

FUSION



- BODY, HEAD & SOCKET MADE BY PRESSURE CASTING.
- MIXING PIPE MADE BY EXTRUDED BRASS / S.S. ROD.
- ECONOMY MODEL

NM CUTTER (3 PIPE)



- BODY, HEAD & SOCKET MADE BY PRESSURE CASTING.
- ALL PIPES ARE OF HEAVY GAUGE.
- BRAZING DONE BY 25% SILVER ROD



info@atularc.com



www.atularc.com

GAS CUTTING NOZZLE



- A & B TYPE
- WEIGHT : 90 GRAMS
- COPPER TO COPPER

FLASH BACK ARRESTOR



- FOR REGULATOR & CUTTER
- FULL FUNCTIONING FLASHBACK ARRESTOR WITH NRV & FLAME DIFFUSOR INSIDE
- APPROX WEIGHT: 300 GRAMS

RUBBER HOSE PIPE



IS : 447:1988



- AVAILABLE FOR OXYGEN & D.A GASES.
- TESTED UPTO 70 KG AIR PRESSURE.
- RUBBER WRAPPING FINISH / I.D. 8.0mm.
- ISI CERTIFIED.

TPR HOSE PIPE



IS : 447:1988



- AVAILABLE FOR OXYGEN & D.A GASES.
- TESTED UPTO 70 KG AIR PRESSURE.
- T.P.R. FINISH / I.D. 8.0mm.
- ISI CERTIFIED.

WELDING CABLE COPPER CONDUCTOR

IS : 9857:1991



CM/L - 2710849

NOMINAL AREA OF CONDUCTOR	NUMBER / DIAMETER OF WIRES IN MM	THICKNESS OF COVERING IN MM	TRS / GENERAL 20%	
16.SQ. MM	510 / 0.20 MM	2.00 MM	210 Amps.	246 Amps.
25 SQ. MM	796 / 0.20 MM	2.00 MM	279 Amps.	343 Amps.
35 SQ. MM	1114 / 0.20 MM	2.00 MM	349 Amps.	403 Amps.
50 SQ. MM	"707 / 0.30 MM OF 1591 / 0.20 MM"	2.20 MM	440 Amps.	509 Amps.
70 SQ. MM	"990 / 0.30 MM OF 2228 / 0.20 MM"	2.40 MM	555 Amps.	643 Amps.
95 SQ. MM	1133 / 0.30 MM	2.60 MM	669 Amps.	774 Amps.






ATULARC®

09

INDUSTRIAL SAFETY GOGGLES

ZOOM (GREY & CLEAR)



SUNTECH 100



SUN 100



SUNLINE



SUNNY JALI



SUNNY JALI FLEXIBLE





MANUFACTURER & EXPORTER OF WELDING EQUIPMENTS

Atul Welding Products (India)

✉ info@atularc.com 🌐 www.atularc.com